


TABLE OF PARAMETERS AVAILABLE FROM KEYBOARD									
	Val.	Description	Def.	Min	Max	UoM		Val.	Description
dir	Sc	Condenser temperature	Read only parameter			°C/°F	ALM	A1	Alarm thresholds (AL, AH) relative to the set point St or absolute:
	Sd	Defrost temperature	Read only parameter			°C/°F		AH	Relative High temperature alarm threshold
	Sm	Outlet temperature	Read only parameter			°C/°F		AL	Relative Low temperature alarm threshold
CU	St	Regulation temperature setpoint	50/122	r1	r2	°C/°F	dMP	AHA	Absolute High temperature alarm threshold
	rd	Regulation temperature differential	2/3.6	0.1/0.2	99.9/179.2	Δ °C/°F		ALA	Absolute Low temperature alarm threshold
	Sth	Humidity set point	90	0.0	100	% rH		Ad	Delay time for high and low temperature alarms (AH, AL)
	rdh	Humidity differential	5	0.1	99.9	Δ % rH		Add	Door alarm delay and high temp. alarm delay after door opening
	IS	Configuration to upload (0: no configuration selected)	-	-	IS_max	-		c0	Compressor, fan and AUX start delay at power on
	r1	Minimum temperature setpoint	-50/-58	-99/-146	r2	°C/°F	Fan	c1	Minimum time between compressor consecutive starts
	r2	Maximum temperature setpoint	50/122	r1	200/392	°C/°F		c2	Minimum compressor OFF time
	m	Neutral zone	4/7.2	0	60/108	°C/°F		F0	Evaporator fan management:
	/4	Virtual probe composition: 0 = Air off (Sm) 100 = Air ON (Sr)	0	0	100	%		F1	Fan activation temperature
	rSc	Restore to Carel settings	0	0	1	-		F2	Fan with compressor off:
Pro	/S	Unit of measure: 0=°C, 1=°F	0	0	1	-	ALARMS	Code	Description
	/6	Decimal point visualization in main mask: 0=Visible, 1=Not visible	0	0	1	-		Code	Description
	/cA	Outlet temperature probe offset calibration	0	-20/-36	20/36	°C/°F		Afr	Frost protection
	/cb	Defrost temperature probe offset calibration	0	-20/-36	20/36	°C/°F		AtS	Restart in pump down
	/cc	Intake temperature probe offset calibration	0	-20/-36	20/36	°C/°F		CE	Configuration writing error
	/nE	Enable user terminal navigation:	0	0	3	-		CHt	High condensing temperature alarm
		0 enabled 1 disabled 2 ON/OFF dis. 3 ON/OFF and Setpoint dis.						cht	High condensing temperature warning
	/t1	Display on user terminal:						dA	Delayed alarm from external contact
		0 Not Config. 3 S3 Value 6 S6 Value 10 Virtual Probe						dor	Door open
		1 S1 Value 4 S4 Value 7 S7 Value Actual Temp.						E1	Probe 1 faulty or disconnected
dEF	/P1	Configuration probe: S1, S2, S4:	2	0	4	-	ALARMS	E2	Probe 2 faulty or disconnected
		0 PT1000 1 PTC 2 NTC 3 NTC-LT 4 NTC-HT						E3	Probe 3 faulty or disconnected
	/P2	Configuration probe: S3/DI1:	5	0	5	-		E4	Probe 4 faulty or disconnected
		0 1, 2, 3, 4 NTC 5 Dig. Input						E5	Probe 5 faulty or disconnected
	d0	Type of defrost:	0	0	4	-		E6	Probe S1H faulty or disconnected
		0 Heater by Temp. 2 Heater by Time 4 Heater by Time						E7	Probe S2H faulty or disconnected
		1 Hot Gas by Temp. 3 Hot Gas by Time with Temp. Control						Ed1	Defrost terminated after maximum time
	di	Defrost interval	8	0	240	hours		Ed2	Defrost on second evaporator terminated after max. time
	dP1	Maximum defrost duration	45	1	240	min		EHI	High power supply voltage alarm
	dt1	End defrost temperature read by Sd	4/39.2	-50/-58	50/122	°C/°F			
HcP	d4	Enabling of defrost at start up: 0=Disabled, 1=Enabled	0	0	1	-	ALARMS	Code	Description
	dd	High temperature alarm delay after defrost	1	1	240	hours		Code	Description
	dd	Dripping time after defrost (fans off)	2	0	15	min		ELO	Low power supply voltage alarm
	rHP	reset HACCP history	0	0	1	-		Etc	Clock error
	Hb	Buzzer: 0=Disabled, 1=Enabled	1	0	1	-		GHI	Generic alarm high threshold
	H0	Serial address	1	1	247	-		GLO	Generic alarm low threshold
	GF1	Configuration up arrow:	0	0	3	-		HA	Type HA HACCP alarm (high temp. during operation)
		0 Off 1 Light 2 Aux 3 Continuous cycle						HF	Type HF HACCP alarm (high temp. after blackout)
	GF2	Configuration down arrow:	0	0	3	-		HI	High temperature
		0 Off 1 Light 2 Aux 3 Continuous cycle						IA	Immediate alarm from external contact



420 - Compressor - Defrost - Fan - Light

421 - Compressor - Defrost - Fan - Alarm

422 - Compressor - Fan - Light - Alarm

423 - Compressor - Resistor - Fan - Alarm

424 - Compressor - Fan - Humidifier

